



Model. SDCMONO

Mains Inter-connectable Carbon Monoxide Detector

Features & Benefits

- Wire Interconnection: max. 40 units (max. 150 meters)
- Electrochemical Sensor: up to 5 years
- Alarm Response Time: 50 PPM (60-90 mins) 100 PPM (10-40 mins) 300 PPM (<3 mins)
- Pre-warning fault signal (signal of disable to function)
- End-of-life signal
- Power & alarm test button
- Low battery warning
- Simple installation

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Bright White
Dimensions (mm)	130 x 75 x 62mm
Electrical	
Power Source	220-240V AC
Operational Current	20mA
Frequency (Hz)	50-60Hz
Operating Temperature	<35mA
Alarm Sound Level	85dB
Ambient Humidity	n/a
Battery Back Up	9V DC Alkaline Battery
Performance Data	
Specifications	EN50291-1:2010+A1:2012
Approvals	BSI, CE, WEEE, ROHS REACH, CE
Construction	
Body Material	Non-flammable ABS plastic
Weight	216g
Warranty Years	5yrs
Others	
Applications	Domestic, commercial applications

