

Model. SDM

Mains Inter-connectable Photoelectric Smoke Detector

Features & Benefits

- Photoelectric sensor for slow smouldering fires
- Silencer (Hush) feature to temporary lower sensitivity when nuisance alarm occurred
- Wire inter-connectable upto 40 units (max. 150 meters)
- Power & alarm test button
- Low battery warning signal & missing battery warning signal for backup model
- Simple installation
- Supplied with fixing kit
- Tamper proof mount

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Bright White
Dimensions (mm)	Ø120 x 54mm
Electrical	
Power Source	220-240V AC
Operational Current	<40mA (mains) 30 uA (9V battery)
Frequency (Hz)	50-60Hz
Operating Temperature	0°C - 40°C
Alarm Sound Level	85dB
Ambient Humidity	10% - 90%
Battery Back Up	9V DC Carbon Zinc Battery
Performance Data	
Specifications	EN14604 2015
Approvals	BSI, CPR, WEEE, RoHS, REACH, CE
Construction	
Body Material	Non-flammable ABS plastic
Weight	128g
Warranty Years	5yrs
Others	
Applications	Domestic, commercial applications

