





IP66 12W ABS+PC Body Circular Bulkhead Outdoor White Fitting

Features & Benefits

- Made to BS EN 60596-2-1
- Can be wall or ceiling mounted
- Constructed from ABS and die-cast polycarbonate diffuser with anti-tamper screws as standard
- Energy saving solution up to 70% more energy efficient
- Latest LED technology and improved lumen output



IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

'	
General Information	
Product Colour/Finish	White
Dimensions (mm)	Ø300x90mm
Ingress Protection	IP66
Electrical	
Input Voltage (V)	230V
Frequency (Hz)	50/60Hz
Wattage (W)	12W
Wattage Equivalent (W)	36W
Dimmable (Y/N)	N
Approvals	CE
Class	II
Performance Data	
Useful Lumen Output	750Lm
Lumens (Per Watt)	83Lm/W
Power Factor	>0.9
Average Lifespan (Hours)	35000Hrs
CRI: Ra	>80
Colour Temperature (K)	4000K
Beam Angle (°)	120°
LED Type	5630
Number of LED (pcs)	24PCS
Energy Rating (ErP)	>A
Sensor	
Emergency	
Construction	
Body Material	ABS
Diffuser Material	Polycarbonate Opal diffuser
Warranty Period (Years)	3Yrs
Other	
Applications	Suitable for 'Car Parks, Commercial & Residential Walkways'

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE

