

## Model. WCS32B

Switch 10Amp 3 Gang 2 Way



### Features & Benefits

- Fits (minimum) box depth 16mm
- Terminal capacity 3x1.5mm<sup>2</sup> (10Amp AX only)
- Front plate depth 10mm (for single & double)
- Supplied with 2 x 30mm M3.5 screws

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Colour/Finish	Chrome
Dimensions (mm)	95 x 95 x 10mm
Front Plate Depth (mm)	8mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	16mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm <sup>2</sup> )	3x1.5mm <sup>2</sup>
Number Earth Terminals	1
Rated Load Capacity (Amps)	10A AX
Frequency (Hz)	50/60Hz
Approvals	BS3676
Kite Mark / ASTA	KM73110
Performance Data	
Switch (1 / 2) etc	3 Switches
Control (1 / 2 Way)	2 Way
Lugs	2
Construction	
Body	Steel plated brass
Insert Colour	Black
Warranty (Years)	25
Other	