

## Model. WCSSK2BUSB

Switched Socket Twin USB



### Features & Benefits

- USB socket charging - 1x2.4A 1x1.2A - 3.6VA
- Fits (minimum) box depth 25mm
- Terminal capacity 4x2.5mm<sup>2</sup> (13Amp only)
- Double pole with 2 earth terminals for convenient installation
- Front plate depth 10mm (for single & double)
- Supplied with 2 x 30mm M3.5 screws

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Colour/Finish	Chrome
Dimensions (mm)	95 x 154 x 10mm
Front Plate Depth (mm)	10mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm <sup>2</sup> )	4x2.5mm <sup>2</sup>
Number Earth Terminals	2
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Number Poles	2 pole with 2 earth terminals
Approvals	BS1363
Kite Mark / ASTA	KM73109
Performance Data	
Outlets (1 / 2) etc	2 Gang (Switched)
Switch (1 / 2) etc	2 Switches
Lugs	2
Construction	
Body	Steel plated brass
Insert Colour	Black
Warranty (Years)	25
Other	