



Model. WL30

30W LED Wall Light

Features & Benefits

- Made to BS EN 60596-2-1
- Can be wall or ceiling mounted
- Constructed from ABS and die-cast polycarbonate diffuser with anti-tamper screws as standard
- Energy saving solution – up to 70% more energy efficient
- Latest LED technology and improved lumen output

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

| General Information | |
|--------------------------|---|
| Product Colour/Finish | Black |
| Dimensions (mm) | Ø360x90mm |
| Ingress Protection | IP65 |
| Electrical | |
| Input Voltage (V) | 220-240V |
| Frequency (Hz) | 50/60Hz |
| Wattage (W) | 30W |
| Wattage Equivalent (W) | 90W |
| Dimmable (Y/N) | N |
| Approvals | CE |
| Class | I |
| Performance Data | |
| Useful Lumen Output | 2400Lm |
| Lumens (Per Watt) | 80Lm/w |
| Power Factor | >90 |
| Average Lifespan (Hours) | 35,000Hrs |
| CRI: Ra | >80 |
| Colour Temperature (K) | 6500k |
| Beam Angle (°) | 120° |
| LED Type | SMD5630 |
| Number of LED (pcs) | 24pcs |
| Energy Rating (ErP) | A |
| Sensor | |
| Emergency | |
| Construction | |
| Body Material | ABS |
| Diffuser Material | Polycarbonate Opal diffuser |
| Warranty Period (Years) | 3Yrs |
| Other | |
| Applications | Suitable for 'Car Parks, Commercial & Residential Walkways' |

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE