

No Image

Model. WMCS45

Metal Clad 45Amp SP Switch to BS3676 BSEN 60669

Features & Benefits

There are currently no features entered for this product item.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

| General Information | |
|--------------------------------------|--------------------|
| Colour/Finish | Silver |
| Dimensions (mm) | 86 x 86 x 42mm |
| Front Plate Depth (mm) | 5mm |
| Fixing Centre (mm) | 60.3mm |
| Minimum Box Depth (mm) | 40mm (Integrated) |
| Electrical | |
| Rated Operating Voltage (v) | 240v |
| Terminal Capacity (mm ²) | 2.5mm ² |
| Rated Load Capacity (Amps) | 45A |
| Frequency (Hz) | 50/60Hz |
| Number Poles | Single Pole |
| Approvals | BS3676 BSEN60669 |
| Kite Mark / ASTA | KM73110 |
| Performance Data | |
| Outlets (1 / 2) etc | 1 |
| Switch (1 / 2) etc | 1 Switch |
| Knockouts | 4 |
| Construction | |
| Body | Urea-formaldehyde |
| Warranty (Years) | 25 |
| Other | |