

Model. WMRCDSP

Single RCD Fuse Spur (Metal Clad)

Features & Benefits

- Test and reset buttons for safety checks
- Manual reset
- Provides residual circuit protection
- Endurance 3000 Cycles min
- Hit-Pot 2000V min Wall Socket
- Break Time 40mS max
- Voltage Surge 4K (100KHz Ring Wave)
- Trip current 30mA
- Single RCD socket

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86x86mm
Front Plate Depth (mm)	n/a
Fixing Centre (mm)	n/a
Minimum Box Depth (mm)	35mm
Ingress Protection (IP)	IP4X
Electrical	
Rated Operating Voltage (v)	240V AC
Terminal Capacity (mm ²)	n/a
Cable Clamp Capacity (mm)	3X2.5 mm
Number Earth Terminals	Single
Rated Load Capacity (Amps)	13A max
Frequency (Hz)	50Hz
Number Poles	2
Approvals	CE, RoHS, Conforms to 7288:1995 & BS1363
Performance Data	
Switch (1 / 2) etc	Unswitched
Flex Inlet	N
Construction	
Warranty (Years)	1yr
Other	
Applications	Suitable for Equipment, Household appliance etc

