



## Model. WMRC DSSK1

RCD Single Switched Socket

### Features & Benefits

- Latching
- Conforms to BS7288:1995 & BS1363
- 1 Gang
- Double Pole
- 30mA Current Tripping
- <40mS Max Tripping Speed

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Colour/Finish	Grey
Dimensions (mm)	85x85x50
Front Plate Depth (mm)	15
Ingress Protection (IP)	IP4X
Electrical	
Rated Operating Voltage (v)	240
Cable Clamp Capacity (mm)	5x2.5mm, 2x4mm, 1x6mm
Number Earth Terminals	2
Rated Load Capacity (Amps)	13
Frequency (Hz)	50
Number Poles	2
Approvals	CE
Maximum Load	13A
Performance Data	
Outlets (1 / 2) etc	1
Switch (1 / 2) etc	1
Control (1 / 2 Way)	1
Knockouts	5x 20mm
Construction	
Body	Steel
Insert Colour	White
Weight	0.91Kg
Warranty (Years)	25
Other	
Applications	Equipment, Household appliance, Commercial, Industrial