

Model. WMS62

Metal Clad Switch 6 Gang 2 Way to BS3676 BSEN 60669

Features & Benefits

There are currently no features entered for this product item.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	Silver
Dimensions (mm)	79 x 138 x 42mm
Front Plate Depth (mm)	5mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	40mm (Integrated)
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	1.5mm ²
Rated Load Capacity (Amps)	10A
Frequency (Hz)	50/60Hz
Approvals	BS 3676 BSEN 60669
Kite Mark / ASTA	KM73110
Performance Data	
Outlets (1 / 2) etc	2 Gang
Switch (1 / 2) etc	6 Switches
Control (1 / 2 Way)	2 Way
Knockouts	8
Construction	
Body	Urea-formaldehyde
Warranty (Years)	25
Other	

