



Model. WMSPSN

Metal Clad Fused Spur Switched 13Amp + Neon to BS1363 pt4

Features & Benefits

There are currently no features entered for this product item.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	Silver
Dimensions (mm)	79 x 79 x 42mm
Front Plate Depth (mm)	5mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	40mm (Integrated)
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	2.5mm ²
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Approvals	BS1363 pt4 AT 13AMP -BS1362 FUSE
Kite Mark / ASTA	KM73109
Performance Data	
Outlets (1 / 2) etc	1 Gang
Switch (1 / 2) etc	1 Switch (with Neon Indicator)
Knockouts	4
Construction	
Body	Urea-formaldehyde
Warranty (Years)	25
Other	