





Model. WMSSK1N

Metal Clad Switched Socket Single 13Amp - DP c/w 2 Earth + Neon

Features & Benefits

There are currently no features entered for this product item.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
 Do not dispose of decommissioned fitting in household waste
 Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	Silver
Dimensions (mm)	79 x 79 x 42mm
Front Plate Depth (mm)	5mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	40mm (Integrated)
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	2.5mm ²
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Approvals	BS1363 pt2
Kite Mark / ASTA	KM73110
Performance Data	
Outlets (1 / 2) etc	1 Gang
Switch (1 / 2) etc	1 Switch (with Neon Indicator)
Knockouts	4
Construction	
Body	Urea-formaldehyde
Warranty (Years)	25yrs
Other	
Applications	Domestic and commercial applications

