

Model. WMSSK2

Metal Clad Twin Switched Socket 13Amp BS1363 pt2

Features & Benefits

- Made to BS1363 pt2 Standard
- Supplied with M3.5 x 20mm long fixing screws
- Sockets supplied with 8 knockouts
- Metal box with two fixed lugs

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	Silver
Dimensions (mm)	79 x 138 x 42mm
Front Plate Depth (mm)	5mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	40mm (Integrated)
Electrical	
Rated Operating Voltage (v)	220-240v AC
Terminal Capacity (mm ²)	4 x 2.5mm ² & 4 x 2.5mm ² earth terminal
Number Earth Terminals	4 x 2.5mm ² & 4 x 2.5mm ² earth terminal
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Number Poles	Single pole
Approvals	CE, RoHS
Kite Mark / ASTA	KM73109
Performance Data	
Outlets (1 / 2) etc	2 Gangs
Switch (1 / 2) etc	2 Switches
Control (1 / 2 Way)	2 ways
Knockouts	8
Construction	
Body	Urea-formaldehyde
Insert Colour	White
Warranty (Years)	25
Other	
Applications	Domestic and commercial applications

