

## Model. WPCT28PH

LED ORCA Wall Pack With Photocell - 28W - IP65

### Features & Benefits

- Variable Output 13-28W
- CCT Feature 3000K or 4000K
- IP65 ingress protection and IK10 impact resistance with Frosted Diffuser
- Photocell

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Product Summary

### Technical Specifications

General Information	
Product Colour/Finish	Anthracite
Dimensions (mm)	265 x 165 x 320
Ingress Protection	IP 65
Electrical	
Input Voltage (V)	220-240
Frequency (Hz)	50/60
Wattage (W)	28
Dimmable (Y/N)	N
Approvals	CE
Class	I
Inrush Current (mA)	15A
Input Protection (Kv)	L-N:2KV LN-E:4KV
Performance Data	
Useful Lumen Output	1700/2500/3500
Lumens (Per Watt)	130
Power Factor	>0.9
Average Lifespan (Hours)	50000
CRI: Ra	80
Colour Temperature (K)	3000/4000
Beam Angle (°)	120
LED Type	SMD2835
Number of LED (pcs)	168
No. Switches (max.)	30000
Sensor	
Emergency	
Construction	
Body Material	Die-cast
Diffuser Material	PC
Weight	2350
Warranty Period (Years)	5
Other	
Applications	Outdoor Areas, Industrial, Courtyard, Landscape Lighting

## LIGHTING DESIGN

### IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

**COMPLETELY FREE**