

Model. WPCT30PH

MAKO 30W LED Mini Wall Pack IP65



Features & Benefits

- CCT Feature
- Photozell
- Frosted Prismatic Diffuser

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Product Summary

Technical Specifications

General Information	
Product Colour/Finish	Brown
Dimensions (mm)	218 x 147 x 78
Ingress Protection	IP 65
Electrical	
Input Voltage (V)	100-240v
Frequency (Hz)	50/60
Wattage (W)	30
Dimmable (Y/N)	N
Approvals	CE
Inrush Current (mA)	30A
Input Protection (Kv)	1.2Kv
Performance Data	
Useful Lumen Output	3300-3600
Lumens (Per Watt)	110-120
Power Factor	>0.9
Average Lifespan (Hours)	50000
CRI: Ra	>80
Colour Temperature (K)	3K/4K/5K
Beam Angle (°)	110
LED Type	Lumileds 2835
Number of LED (pcs)	80
No. Switches (max.)	100000
Sensor	
Emergency	
Construction	
Body Material	Aluminium
Diffuser Material	PC
Weight	0.9Kg
Warranty Period (Years)	5yrs
Other	
Applications	Outdoor Areas, Industrial, Courtyard, Landscape Lighting

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE