

Model. WPS424LED

4' Single Anti-Corrosive Fitting with Frosted Diffuser 24W

Features & Benefits

- Made to BS EN 60309-2
- Fittings with anti-corrosive and frosted diffuser for high Lumen output
- Optional spare Opal diffuser for single and twin fitting
- Polycarbonate body provides protection for moisture, grease, and UV radiation
- SMD LED chip
- Mounted direct on wall or suspended by chains
- Optional meta clips available for extra security construction.

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	1232x85x71mm
Cut-Hole Ø (mm)	n/a
Ingress Protection	IP65
Electrical	
Input Voltage (V)	240V AC
Frequency (Hz)	50/60Hz
Wattage (W)	24W
Wattage Equivalent (W)	120W
Dimmable (Y/N)	N
Approvals	CE / GS, EMC, RoHS, UL
Class	n/a
Performance Data	
Useful Lumen Output	2280Lm
Lumens (Per Watt)	95Lm/w
Power Factor	>0.9
Average Lifespan (Hours)	30,000Hrs
CRI: Ra	>80
Colour Temperature (K)	5000K
Beam Angle (°)	120°
LED Type	SMD
Energy Rating (ErP)	A
Sensor	
Sensor Interval (mins)	n/a
Sensor Range (Mtrs / °)	n/a
Emergency	
Emergency Output (W)	n/a
Emergency Period (Hours)	n/a
Construction	
Body Material	Polycarbonate
Diffuser Material	4ft. Frosted diffuser
Weight	1.8kg
Warranty Period (Years)	3Yrs
Other	
Applications	Bars, restaurants, cafe', shops, garages, workshops, schools, spas and domestic use.

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE