

Model. WPS648LED

6' Single Anti-Corrosive Fitting with Frosted Diffuser 48W

Features & Benefits

- Fittings with anti-corrosive and frosted diffuser for high Lumen output
- Optional spare Opal diffuser for single and twin fitting with metal clips for extra security
- New design polycarbonate body provides protection for moisture, grease and UV radiation
- Complete with SMD LED chip and can be mounted direct on wall or suspended by chains

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	1832x85x71mm
Ingress Protection	IP65
Electrical	
Input Voltage (V)	240V AC
Frequency (Hz)	50/60Hz
Wattage (W)	48W
Wattage Equivalent (W)	240W
Dimmable (Y/N)	N
Approvals	CE / GS, EMC, RoHS, UL
Class	I
Performance Data	
Useful Lumen Output	4560Lm
Lumens (Per Watt)	95Lm/W
Power Factor	>0.9
Average Lifespan (Hours)	35,000Hrs
CRI: Ra	>80
Colour Temperature (K)	6500K
Beam Angle (°)	120°
LED Type	SMD
Energy Rating (ErP)	A
Sensor	
Sensor Interval (mins)	n/a
Sensor Range (Mtrs / °)	n/a
Emergency	
Emergency Output (W)	n/a
Emergency Period (Hours)	n/a
Construction	
Body Material	Polycarbonate
Diffuser Material	6ft Frosted diffuser
Weight	2.9Kg
Warranty Period (Years)	3Yrs
Other	
Applications	Domestic and commercial applications

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE