

Model. WRCDMSSK2

RCD Metal Clad Twin Switched Socket with Twin Earth Terminal

Features & Benefits

- Prevents fatal electric shock on a person by reducing to "safe" levels the value and the time a person is exposed to current flowing through the body
- Latching, passive type
- No need to reset after power loss

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	Grey
Dimensions (mm)	146x 86x50mm
Front Plate Depth (mm)	5mm
Minimum Box Depth (mm)	35mm
Ingress Protection (IP)	IP4X
Electrical	
Rated Operating Voltage (v)	240V
Cable Clamp Capacity (mm ²)	5 x 2.5mm ²
Number Earth Terminals	2
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Number Poles	2
Approvals	CE BS7288 BS1363
Maximum Load	13A
Performance Data	
Outlets (1 / 2) etc	2
Switch (1 / 2) etc	2
Knockouts	9 x 20mm
Flex Inlet	20mm k/o
Construction	
Body	Metal clad
Insert Colour	White
Warranty (Years)	25yrs
Other	
Applications	Domestic and commercial applications

