

Model. WRCDSK2

RCD Twin Unswitched Socket (Moulded)

Features & Benefits

- 30mA Current Tripping
- <40mS max Tripping Speed
- 13Amp 3 Pin 240v 50Hz
- IP Rating IP4X
- Latching :Mechanical, no need to reset after the power loss

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Product Summary

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	145x85x35
Front Plate Depth (mm)	15
Minimum Box Depth (mm)	35
Ingress Protection (IP)	IP4X
Electrical	
Rated Operating Voltage (v)	240
Number Earth Terminals	2
Rated Load Capacity (Amps)	13
Frequency (Hz)	50-60
Number Poles	2
Approvals	Conforms to 7288:1995 & BS1363
Performance Data	
Outlets (1 / 2) etc	2
Switch (1 / 2) etc	Reset and Test buttons
Control (1 / 2 Way)	Latching
Construction	
Body	Plastic
Insert Colour	White
Warranty (Years)	25
Other	
Applications	Suitable for Equipment, Household appliance etc

