

Model. WRCDSSK1

RCD Single Switched Socket



Features & Benefits

- Prevents fatal electric shock on a person by reducing to “safe” levels the value and the time a person is exposed to current flowing through the body
- Can be either mounted in an outlet box or flush mounted
- Mechanical latching prevents tripping on power failure
- On/Off Indicator

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	85x85x30mm
Front Plate Depth (mm)	10mm
Minimum Box Depth (mm)	35mm
Ingress Protection (IP)	IP20
Electrical	
Rated Operating Voltage (v)	220-240
Cable Clamp Capacity (mm)	2.5
Rated Load Capacity (Amps)	240V
Frequency (Hz)	50/60Hz
Number Poles	2
Conductor Size (mm ²)	3 x 2.5mm ²
Approvals	CE BS7288 BS1363
Maximum Load	13A
Performance Data	
Outlets (1 / 2) etc	1
Switch (1 / 2) etc	1
Construction	
Body	Plastic
Insert Colour	white
Weight	0.164Kg
Warranty (Years)	25yrs
Other	
Applications	Domestic and commercial applications