



## Model. WRCDSSK2

RCD Twin Switched Socket with Two Earth Terminals

## Features & Benefits

- Provides protection against electric shock
- Complete isolation for the mains supply once tripped
- latchting type, no need to reset

## Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
  Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

## **Technical Specifications**

General Information	
Colour/Finish	White
Dimensions (mm)	145x85x40mm
Front Plate Depth (mm)	15mm
Fixing Centre (mm)	120mm
Minimum Box Depth (mm)	35mm
Electrical	
Rated Operating Voltage (v)	240V
Terminal Capacity (mm <sup>2</sup> )	2.5mm <sup>2</sup>
Number Earth Terminals	2
Rated Load Capacity (Amps)	13
Frequency (Hz)	50/60Hz
Number Poles	Double poles
Approvals	CE, RoHS, BS7288, BS1363
Performance Data	
Outlets (1 / 2) etc	2
Switch (1 / 2) etc	Test button and reset button
Construction	
Body	White plastic
Weight	200g
Warranty (Years)	1Yr
Other	

Applications

Household appliances, office, garden



