

Model. WCSSK1B

Switched Socket Single 13Amp



Features & Benefits

- Fits (minimum) box depth 25mm
- Terminal capacity 4x2.5mm² (13Amp only)
- Double pole with 2 earth terminals for convenient installation
- Front plate depth 10mm (for single & double)
- Supplied with 2 x 30mm M3.5 screws

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

| General Information | |
|--------------------------------------|-------------------------------|
| Colour/Finish | Satin Chrome |
| Dimensions (mm) | 95 x 95 x 10mm |
| Front Plate Depth (mm) | 10mm |
| Fixing Centre (mm) | 60.3mm |
| Minimum Box Depth (mm) | 25mm |
| Electrical | |
| Rated Operating Voltage (v) | 240v |
| Terminal Capacity (mm ²) | 4x2.5mm ² |
| Number Earth Terminals | 1 |
| Rated Load Capacity (Amps) | 13A |
| Frequency (Hz) | 50/60Hz |
| Number Poles | 2 pole with 2 earth terminals |
| Approvals | BS1363 |
| Kite Mark / ASTA | KM73109 |
| Performance Data | |
| Outlets (1 / 2) etc | 1 Gang (Switched) |
| Switch (1 / 2) etc | 1 Switch |
| Lugs | 2 |
| Construction | |
| Body | Steel plated brass |
| Insert Colour | Black |
| Warranty (Years) | 25 |
| Other | |