

Model. XF4P

4" Extractor Fan Pullcord (FE4P)



Features & Benefits

- Class II (double insulated)
- Air movement: 80 cubic Mtrs/hr
- Rated: 48.6(dB)
- Power consumption: 20W (max)
- Complete with comprehensive installation instructions
- Suitable for the ventilation of toilets and bathrooms in accordance with IEE & Building regulations

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	165 x 154 x 88
Ingress Protection (IP)	IPX4
Electrical	
Power Consumption	20W
Input Voltage (V)	220-240V
Frequency (Hz)	50Hz
Class	II
Approvals	BS EN60335-1: 2012, CE, GS approved
Performance Data	
Timer	Continuous
Suitable mounting position	Wall
Air Volume/Velocity (cbm)	80
Noise level (dB)	48.6(dB)
Construction	
Other	
Applications	Suitable for the ventilation of toilets and bathrooms in accordance with IEE & Building regulations