

Model. CEDSSK1

1 Gang Switched Socket 13Amp



Features & Benefits

- BS EN1363 AC only Contact Gap - 3mm
- Minimum Depth - Plastic / PVC Box - 25mm
- Terminal Capacity - 4 x 2.5mm² (13Amp Only)
- Supplied With M3.5 x 30mm Fixing Screws

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.03mm
Minimum Box Depth (mm)	Plastic / PVC Box - 25mm
Electrical	
Rated Operating Voltage (v)	220-250vAC
Terminal Capacity (mm ²)	4x2.5mm ²
Number Earth Terminals	1
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Number Poles	1
Approvals	BS 1363 pt 2
Kite Mark / ASTA	KM73109
Performance Data	
Outlets (1 / 2) etc	1 Gang
Switch (1 / 2) etc	1 Gang
Control (1 / 2 Way)	1 Way
Construction	
Body	Urea Formaldehyde
Weight	85g
Warranty (Years)	25
Other	
Applications	Domestic, Commercial