

## Model. CEDSSK2DP

Double Pole Twin Switched Socket c/w 2 Earth

### Features & Benefits

- BS EN1363 AC only contact gap - 3mm
- Large capacity for easy terminal installation
- Supplied with M3.5 x 30mm Fixing Screws
- Fireproof moulded classic design
- Terminals accept up to 4 x 2.5mm<sup>2</sup> cables
- Dual Earth terminals for high integrity earthing

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 146 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	Plastic / PVC Box - 25mm
Electrical	
Rated Operating Voltage (v)	13Amp
Terminal Capacity (mm <sup>2</sup> )	4 x 2.5mm <sup>2</sup>
Number Earth Terminals	2
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Number Poles	Double Pole
Approvals	BS 1363 pt 2
Kite Mark / ASTA	KM73109
Performance Data	
Outlets (1 / 2) etc	2 Gang
Switch (1 / 2) etc	2 switches
Control (1 / 2 Way)	2 Way
Lugs	N
Knockouts	N
Construction	
Body	Urea-formaldehyde
Insert Colour	White
Weight	200g
Warranty (Years)	25
Other	
Applications	Domestic, commercial applications

