

Model. CEDSSK2N

2 Gang Switched Socket 13Amp - Single Pole with Neon

Features & Benefits

- BS EN1363 AC only
- Large capacity for easy terminal installation, Contact Gap - 3mm
- Fireproof moulded classic design
- Terminals accept up to 4 x 2.5mm² cables
- Dual Earth terminals for high integrity earthing

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 146 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	Plastic / PVC Box - 25mm
Electrical	
Terminal Capacity (mm ²)	4 x 2.5mm ²
Number Earth Terminals	2
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Number Poles	1
Approvals	BS 1363 pt 2
Kite Mark / ASTA	KM73109
Performance Data	
Outlets (1 / 2) etc	2 Gang
Switch (1 / 2) etc	2 Gang
Control (1 / 2 Way)	2 Way
Lugs	N
Knockouts	N
Construction	
Body	Urea Formaldehyde
Insert Colour	White insert
Weight	200g
Warranty (Years)	25
Other	
Applications	Domestic, commercial applications

