

## Model. CEDSSK2USB

2 Gang Switched Socket c/w USB Charging Ports



### Features & Benefits

- BS EN1363 AC only
- Contact Gap - 3mm
- Minimum Depth - Plastic / PVC Box - 25mm
- Terminal Capacity - 4 x 2.5mm<sup>2</sup> (13Amp only)
- Supplied with M3.5 x 30mm Fixing Screws

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 146 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	Plastic / PVC Box - 25mm
Electrical	
Terminal Capacity (mm <sup>2</sup> )	4X2.5mm <sup>2</sup>
Number Earth Terminals	2 Earth Terminals
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Number Poles	1
Approvals	BS 1363 pt 2
Kite Mark / ASTA	KM73109
Performance Data	
Outlets (1 / 2) etc	2 Gang
Switch (1 / 2) etc	2 Gang
Control (1 / 2 Way)	2 Way
Lugs	N
Knockouts	N
Construction	
Body	Urea-formaldehyde
Insert Colour	White insert
Weight	250g
Warranty (Years)	25
Other	
Applications	Domestic, commercial applications