





Cooker Outlet Plate 45A

Features & Benefits

- Cable clamp accommodates 4mm² to 16mm² cable for 45Amp
- Terminal capacity 3 x 2.5mm² for 20/25Amp
- Supplied with M3.5 x 30mm fixing screws



IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
 Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information		
Colour/Finish	White	
Dimensions (mm)	86 x 86 x 11mm	
Front Plate Depth (mm)	11mm	
Fixing Centre (mm)	60.3mm	
Minimum Box Depth (mm)	47mm	
Electrical		
Rated Operating Voltage (v)	250v	
Terminal Capacity (mm²)	1 x 10mm ²	
Cable Clamp Capacity (mm)	4mm² to 16mm²	
Rated Load Capacity (Amps)	45A	
Frequency (Hz)	50/60Hz	
Kite Mark / ASTA	ASTA (lic. 923)	
Performance Data		
Knockouts	1 to bottom	
Flex Inlet	Υ	
Construction		
Body	Urea Formaldehyde	
Weight	152g	
Warranty (Years)	25	
Other		

