





Cooker Switch Socket 45A (Double Pole)

Features & Benefits

- 45Amp D.P. main switch with 13Amp socket
- Terminal capacity 2 x 10mm², 1 x 10mm² each
 Supplied with M3.5 x 30mm fixing screws



IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

'	
General Information	
Colour/Finish	White
Dimensions (mm)	86 x 146 x 11mm
Front Plate Depth (mm)	11mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	250v
Terminal Capacity (mm²)	1 x16mm²
Number Earth Terminals	2
Rated Load Capacity (Amps)	45A / 13A (socket)
Frequency (Hz)	50/60Hz
Number Poles	2 (Double)
Approvals	ASTA
Kite Mark / ASTA	lic. 922
Performance Data	
Outlets (1 / 2) etc	1 Gang
Switch (1 / 2) etc	2 Gang
Construction	
Body	Urea Formaldehyde
Weight	197g
Warranty (Years)	25
Other	

