

Model. CUB10SP

10A-SP MCB



Features & Benefits

- Provides positive contact indication in accordance with IEE wiring regulations
- Provides protection against short circuits and overload with thermal magnetic operation
- Manufactured to BS EN 60898
- Type B characteristics
- Line protective switches
- No tools required for mounting or dismantling
- Supports fast and convenient removal from the assembly

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Grey
Dimensions (mm)	40x18x80mm (45mm Projection)
Electrical	
Rated Voltage	230 - 240V
Frequency (Hz)	50/60Hz
Terminal Capacity (mm ²)	Up to 35mm ²
Performance Data	
Specifications	IEC 60898-2
AMPS	10Amp
Poles	Single
Type	B
Breaking Capacity	6kA SP
Approvals	CE, RoHS
Construction	
Weight	0.115Kg
Warranty Years	1Yrs
Body Material	Acrylic
Others	
Applications	Domestic and commercial applications