

Model. EMPN3ST

3W Emergency Exit Panel with Self-Test



Features & Benefits

- Can Be Maintained or Non-Maintained
- Self Testing

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Product Summary

Technical Specifications

General Information	
Product Colour/Finish	White
Dimensions (mm)	310 x 230 x 35
Ingress Protection	IP 20
Electrical	
Input Voltage (V)	220 - 240
Frequency (Hz)	50-60
Wattage (W)	3
Dimmable (Y/N)	N
Approvals	CE
Class	II
Performance Data	
Useful Lumen Output	80
Lumens (Per Watt)	66
Power Factor	0.8
Average Lifespan (Hours)	30000
CRI: Ra	86.1
Colour Temperature (K)	6000
Beam Angle (°)	120
LED Type	SMD2835
Number of LED (pcs)	16
Energy Rating (ErP)	A+
Sensor	
Emergency	
Emergency Output (W)	1
Emergency Period (Hours)	3
Construction	
Body Material	PC
Diffuser Material	PC
Weight	0.83Kg
Warranty Period (Years)	3
Other	
Applications	Commercial, Cinemas, Corridors, Stair Wells, Emergency Escapes

LIGHTING DESIGN

IMPORTANT!

We now offer a full lighting design service exclusively to all our customers

COMPLETELY FREE