

Model. AXMS11

10A Switch 1 Gang / 1 Way - ASTA



Features & Benefits

- 10Amp (X rated) suitable for inductive load
- Supplied with M3.5 x 25mm fixing screws
- Minimum Depth - Metal/Plastic/PVC Box 16mm
- Terminal Capacity - 3x1.5mm²

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	16mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	3 x 1.5mm ²
Rated Load Capacity (Amps)	10A
Frequency (Hz)	50/60Hz
Number Poles	1
Kite Mark / ASTA	ASTA
Performance Data	
Switch (1 / 2) etc	1 Gang
Control (1 / 2 Way)	1 Way
Construction	
Body	Urea Formaldehyde
Weight	71.5g
Warranty (Years)	25
Other	
Applications	Domestic and commercial applications