





45Amp Socket & Switch



- Made to BS1363 Standard
- Double Pole with 2 Earth Terminals for convenient installation
- Kitemark approved licence no. KM73110



IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	Satin Chrome
Dimensions (mm)	95X95X10mm
Front Plate Depth (mm)	1mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	45Amps
Terminal Capacity (mm²)	10mm ²
Number Earth Terminals	2
Rated Load Capacity (Amps)	220-240
Frequency (Hz)	50/60Hz
Number Poles	Double poles
Approvals	BS3676 AC O
Kite Mark / ASTA	KM73110
Performance Data	
Outlets (1 / 2) etc	1 Gang
Switch (1 / 2) etc	2 Gang
Construction	
Body	Stainless steel
Insert Colour	Black
Warranty (Years)	15yrs
Other	
Applications	Suitable for domestic, commercial and Industrial applications

