

## Model. AXMS20

Switch 20A (Double Pole)



### Features & Benefits

- Flex outlet at lower edge by knockout - choice of use
- Supplied with M3.5 x 30mm fixing screws
- Cable Clamp accommodates 2.5mm<sup>2</sup> flexible cable
- Minimum Depth - Metal/Plastic/PVC Box 25mm
- Terminal capacity - 3 x 2.5mm<sup>2</sup>, 4 x 2.5mm<sup>2</sup> (Earth)

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

| General Information                  |   |
|--------------------------------------|---|
| Colour/Finish                        | White   |
| Dimensions (mm)                      | 86 x 86 x 9mm                                   |
| Front Plate Depth (mm)               | 9mm   |
| Fixing Centre (mm)                   | 60.3mm  |
| Minimum Box Depth (mm)               | 25mm  |
| Electrical                           |   |
| Rated Operating Voltage (v)          | 240v  |
| Terminal Capacity (mm <sup>2</sup> ) | 3 x 2.5mm <sup>2</sup> , 4 x 2.5mm <sup>2</sup> |
| Rated Load Capacity (Amps)           | 20A   |
| Frequency (Hz)                       | 50/60Hz   |
| Number Poles                         | 2   |
| Performance Data                     |   |
| Switch (1 / 2) etc                   | 1 Gang  |
| Knockouts                            | 1 at bottom                                     |
| Construction                         |   |
| Body                                 | Urea Formaldehyde                               |
| Warranty (Years)                     | 25  |
| Other                                |   |