

Model. AXMS20N

Switch 20A + Neon (Double Pole)



Features & Benefits

- Flex outlet at lower edge by knockout - choice of use
- Supplied with M3.5 x 30mm fixing screws
- Cable Clamp accommodates 2.5mm² flexible cable
- Minimum Depth - Metal/Plastic/PVC Box 25mm
- Terminal capacity - 3 x 2.5mm², 4 x 2.5mm² (Earth)

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm ²)	3 x 2.5mm ² , 4 x 2.5mm ²
Rated Load Capacity (Amps)	20A
Frequency (Hz)	50/60Hz
Number Poles	2
Performance Data	
Knockouts	1 at bottom
Construction	
Body	Urea Formaldehyde
Warranty (Years)	25
Other	