

## Model. AXMSARC

10A Archtrave Switch 1 Gang 2 Way



### Features & Benefits

- 10Amp (X rated) suitable for inductive load
- Supplied with M3.5 x 25mm fixing screws
- Minimum Depth - Metal/Plastic/PVC Box 16mm
- Terminal Capacity - 3x1.5mm<sup>2</sup>
- Three Pole Isolators provide isolation of fans for maintenance or repair without isolation of complete circuit

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 32 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm (vertical)
Minimum Box Depth (mm)	16mm
Electrical	
Rated Operating Voltage (v)	240v
Terminal Capacity (mm <sup>2</sup> )	3x1.5mm <sup>2</sup>
Rated Load Capacity (Amps)	10A
Frequency (Hz)	50/60Hz
Performance Data	
Switch (1 / 2) etc	1 Gang
Control (1 / 2 Way)	2 Way
Construction	
Body	Urea Formaldehyde
Warranty (Years)	25
Other	