

Model. AXMSK1

1 Gang Unswitched Socket 13A



Features & Benefits

- Contact Gap - 3mm
- Minimum Depth - Plastic/PVC box - 25mm
- Terminal Capacity - 4x2.5mm² (13Amp only)
- 1 Earth Terminals for easy installation - Single Pole
- Supplied with M3.5 x 30mm fixing screws
- Front Plate Depth - Single Pole - 9mm

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 9mm
Front Plate Depth (mm)	9mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	250v
Terminal Capacity (mm ²)	3 x 2.5mm ²
Number Earth Terminals	1
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50Hz
Number Poles	1 (Single)
Kite Mark / ASTA	ASTA (lic.914)
Performance Data	
Outlets (1 / 2) etc	1 Gang
Construction	
Body	Urea Formaldehyde
Weight	90g
Warranty (Years)	25
Other	