





Model. AXMSP

Spur 13A - ASTA

Features & Benefits

- Flex outlet at lower edge by knockout (choice of use)
- Cable clamp accommodates 2.5mm² flexible cable
- Fitted with 13Amp Fuse unless specified otherwise
- Minimum Depth Metal/Plastic/PVC Box 25mm
- Terminal capacity 3 x 2.5mm², 4 x 2.5mm² (Earth)
 Supplied with M3.5 x 30mm fixing screws

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
 Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Colour/Finish	White
Dimensions (mm)	86 x 86 x 13mm
Front Plate Depth (mm)	13mm
Fixing Centre (mm)	60.3mm
Minimum Box Depth (mm)	25mm
Electrical	
Rated Operating Voltage (v)	250v
Terminal Capacity (mm ²)	3 x 2.5mm ²
Cable Clamp Capacity (mm)	2.5mm ²
Number Earth Terminals	1 (single)
Rated Load Capacity (Amps)	13A
Frequency (Hz)	50/60Hz
Kite Mark / ASTA	ASTA (lic. 915)
Performance Data	
Knockouts	1 x bottom
Flex Inlet	2
Construction	
Body	Urea Formaldehyde
Weight	101g
Warranty (Years)	25
Other	

