

## Model. FSSK2BN

13Amp 2 Gang Switched Socket



### Features & Benefits

- Made to BS1363 Standard
- Double Pole with 2 Earth Terminals for convenient installation
- Kitemark approved - licence no. KM73109

### Safety Information

**IMPORTANT** - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
- Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

### Technical Specifications

General Information	
Colour/Finish	Satin Chrome
Dimensions (mm)	95x154x10mm
Front Plate Depth (mm)	1mm
Fixing Centre (mm)	120.6mm
Minimum Box Depth (mm)	25-35mm
Ingress Protection (IP)	IP20
Electrical	
Rated Operating Voltage (v)	13Amp
Terminal Capacity (mm <sup>2</sup> )	2.5mm <sup>2</sup>
Number Earth Terminals	1
Rated Load Capacity (Amps)	220-240V AC
Frequency (Hz)	50/60Hz
Number Poles	Single pole
Approvals	BS1363
Kite Mark / ASTA	KM73109
Performance Data	
Outlets (1 / 2) etc	2 Gang
Switch (1 / 2) etc	2 Gang
Control (1 / 2 Way)	2
Flex Inlet	Black
Construction	
Body	Chrome plated aluminium
Insert Colour	BLK
Warranty (Years)	15yrs
Other	
Applications	Suitable for domestic, commercial and Industrial applications