



Dry PTFE Lubricating agent (L051)

This spray creates a PTFE dry coat on treated parts; it doesn't leave bots and it doesn't hold dust. Able to resist very high and very low temperatures.



Quantity	400 ml
Barcode	EAN 13: 8034108890098
Box / Case	12 pz

DRY PTFE LUBRICATING AGENT – This lubricant goes on dry, is water-repellent, and anti-adhesive. It does not withhold dust and it does not stain. It forms a dry and flexible layer of PTFE on the treated part that adheres tightly to metal, wood, and plastic, etc. Temperature-resistant between -80°C/-112°F and +260°C/500°F. It provides protection against corrosion. Ideal for drive chains, threads, rollers, belts, guides and heavy-duty tools, etc.

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Light white
Odour	Characteristic of solvent
Relative density	at 20°C 0,61 ÷ 0,65 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Melting point	ASTM D4591 deg C 334,70
PTFE Average particle size	INTERN micron 3,0 +/- 2
Specific gravity	ASTM D4894 g/cm ³ 2,18 +/- 0,05
Melting point PTFE	327°C \cap 340 °C
Maximum temperature	400°C(peaks)

HOW TO USE: shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT