

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: V400/CAR
 Product name: FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL
 UFI: 4H80-10Y4-900A-5UCW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Aerosol paint.

Identified Uses	Industrial	Professional	Consumer
Consumer	-	-	✓
Industrial Use	✓	-	-
Professional Use	-	✓	-

1.3. Details of the supplier of the safety data sheet

Name: AMBRO-SOL SRL SOCIETA' BENEFIT
 Full address: Via per Pavone del Mella n.21
 District and Country: 25020 Cigole (BS)
 Italia
 Tel. +39 030 9959674
 Fax +39 030 959265

e-mail address of the competent person
 responsible for the Safety Data Sheet

regulatory@ambro-sol.com

1.4. Emergency telephone number

For urgent inquiries refer to

IT - Centro Antiveleni e Centro Nazionale di Informazione Tossicologica: Tel. 0382 24444 (IRCCS Fondazione Salvatore Maugeri - Pavia)
 IT - Centro Antiveleni di Milano: Tel. 02 66101029 (Ospedale Niguarda Ca' Granda - Milano)
 IT - Centro Antiveleni di Roma: Tel. 06 3054 343 (Policlinico Universitario A. Gemelli IRCCS - Roma)
 IT - Centro Antiveleni di Bergamo: Tel. 800 883300 (ASST Papa Giovanni XXIII - Bergamo)
 IT - Centro Antiveleni di Firenze: Tel. 055 794 7819 (Azienda Ospedaliera Universitaria Careggi - Firenze)
 IT - Centro Antiveleni di Napoli: Tel. 081 5453333 (Azienda Ospedaliera A. Cardarelli - Napoli)
 AT - Vergiftungsinformationszentrale (VIZ): Tel. +43 01 406 4343 (Austria)
 BE - Belgisch Antigifcentrum: Tel. 070 245245 (Belgium)
 BG - НАЦИОНАЛЕН ЦЕНТЪР ПО ТОКСИКОЛОГИЯ: Tel. +359 2 9154 233 (Bulgaria)
 HR - Centar za kontrolu otrovanja: Tel. +385 1 2348342 (Croatia)
 CY - Τμήμα Επιθεώρησης Εργασίας (TEE): Tel. 1401 (Cyprus)
 CZ - Toxikologické informační středisko (TIS): Tel. +420 224 919 293 or +420 224 915 402 (Czech Republic)
 DK - Giftlinjen: Ring 82 12 12 12 (Denmark)
 EE - Mürgistusteabekeskus: Tel. 16662 (Estonia)
 FI - Myrkytystietokeskus: Tel. 0800 147 111 or 09 471 977 (Finland)
 FR - ORFILA (INRS): Tél. +33 (0) 1 45 42 59 59 (France)

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

DE - Giftnotruf der Charité Universitätsmedizin Berlin: Tel. +49 030 19240 (Germany)
 GR - Κέντρο Δηλητηριάσεων: Τηλ. 210 7793777 (Greece)
 HU - Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ): Tel. +36 80 20 1199 (Hungary)
 IS - Eitrunarmiðstöð: Tel. 543 2222 (Iceland)
 IE - National Poisons Information Centre (NPIC): Tel. 01 8092566 or 01 8379964 (Republic of Ireland)
 LV - Latvian Poisons Information Centre: Tel. +371 67042473 (Latvia)
 LT - Apsinuodijimų Informacijos biuras: Tel. 8-5 236 2052 (Lithuania)
 LU - Giftinformationszentrum: Tel. +352 8002 5500 (Luxembourg)
 NL - Nationaal Vergiftigingen Informatie Centrum (NVIC): Tel. 030 274 88 88 (Netherlands)
 NO - Giftinformasjonen: Tel. 22 9 13 00 (Norway)
 PL - Pomorskie Centrum Toksykologii: Tel. +58 682 04 04 (Poland)
 PT - Centro de Informação Antivenenos (CIAV): Tel. 800 250 250 (Portugal)
 RO - Biroul RSI Si Informare Toxicologica: Tel. 021 318 36 06 (Romania)
 SK - Národné Toxikologické informačné centrum (NTIC): Tel. 02 5477 4166 (Slovakia)
 SI - Center za klinično toksikologijo in farmakologijo: Tel. 112 (Slovenia)
 ES - Servicio de Información Toxicológica (SIT) España: Tel.+34 91 562 04 20 (Spain)
 SE - Giftinformationscentralen: Tel. 112 (Sweden)
 CH - Schweizerisches Toxikologisches Informationszentrum (STIZ): Tel. +41 145 (Switzerland)
 GB - National Poisons Information Service (NPIS) Tel. 0344 892 0111 (United Kingdom)
 Members of the Public: NHS 111 (England), NHS 24 (Scotland) or NHS Direct (Wales)

SECTION 2. Hazards identification**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:**Signal words:**

Danger

AMBRO-SOL SRL SOCIETA' BENEFIT

Revision nr. 7

Dated 10/11/2022

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

Printed on 10/11/2022

Page n. 3/32

Replaced revision:6 (Dated: 26/08/2021)

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P501	Dispose of contents/container in accordance with local regulations.
P102	Keep out of reach of children.
P211	Do not spray on an open flame or other ignition source.
P271	Use only outdoors or in a well-ventilated area.

Contains:	Acetone
	N-butyl acetate
	Ethyl methyl ketone
	Hydrocarbons, C9, aromatics

VOC (Directive 2004/42/EC) :

Special finishes.

VOC given in g/litre of product in a ready-to-use condition :	712,00
Limit value:	840,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Dimethyl ether		
INDEX 603-019-00-8	$39 \leq x < 43$	Flam. Gas 1A H220, Press. Gas H280
EC 204-065-8		
CAS 115-10-6		
REACH Reg. 01-2119472128-37-		

AMBRO-SOL SRL SOCIETA' BENEFIT			Revision nr. 7
V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL			Dated 10/11/2022
			Printed on 10/11/2022
			Page n. 4/32
			Replaced revision:6 (Dated: 26/08/2021)
XXXX			
Acetone			
INDEX 606-001-00-8	15 ≤ x < 19	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066	
EC 200-662-2			
CAS 67-64-1			
REACH Reg. 01-2119471330-49-			
XXXX			
N-butyl acetate			
INDEX 607-025-00-1	7 ≤ x < 9	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066	
EC 204-658-1			
CAS 123-86-4			
REACH Reg. 01-2119485493-29-			
XXXX			
Xylene (Mixture of isomers)			
INDEX 601-022-00-9	5 ≤ x < 7	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C LD50 Dermal: >1700 mg/kg, STA Inhalation mists/powders: 1,5 mg/l	
EC 215-535-7			
CAS 1330-20-7			
REACH Reg. 01-2119488216-32-			
XXXX			
Ethyl methyl ketone			
INDEX 606-002-00-3	3 ≤ x < 5	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066	
EC 201-159-0			
CAS 78-93-3			
REACH Reg. 01-2119457290-43-			
XXXX			
Hydrocarbons, C9, aromatics			
INDEX -	2,5 ≤ x < 3	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: P	
EC 918-668-5			
CAS -			
REACH Reg. 01-2119455851-35-			
XXXX			
2-Butoxyethanol			
INDEX 603-014-00-0	1 ≤ x < 3	Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315 LD50 Oral: 1200 mg/kg, STA Inhalation mists/powders: 0,501 mg/l	
EC 203-905-0			
CAS 111-76-2			
REACH Reg. 01-2119475108-36-			
XXXX			
Solvent naphtha (petroleum), light arom.			
INDEX 649-356-00-4	1 ≤ x < 2,5	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, Classification note according to Annex VI to the CLP Regulation: P	
EC 265-199-0			
CAS 64742-95-6			
REACH Reg. 01-2119455851-35-			
XXXX			
2-methoxy-1-methylethyl acetate			
INDEX 607-195-00-7	1 ≤ x < 3	Flam. Liq. 3 H226	

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

EC 203-603-9

CAS 108-65-6

REACH Reg. 01-2119475791-29-XXXX

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

INDEX 022-006-00-2

 $1 \leq x < 3$

Carc. 2 H351, EUH211, EUH212, Classification note according to Annex VI to the CLP Regulation: 10, V, W

EC 236-675-5

CAS 13463-67-7

Ethylbenzene

INDEX 601-023-00-4

 $1 \leq x < 3$ Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373
STA Inhalation mists/powders: 1,5 mg/l

EC 202-849-4

CAS 100-41-4

REACH Reg. 01-2119489370-35-XXXX

Isobutyl acetate

INDEX 607-026-00-7

 $0 \leq x < 0,5$

Flam. Liq. 2 H225, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: C

EC 203-745-1

CAS 110-19-0

REACH Reg. 01-2119488971-22-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 40,00 %

Solvent naphtha (petroleum), light arom.

** Solvent naphtha (petroleum), light arom. Low boiling point naphtha - unspecified [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]**SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

AMBRO-SOL SRL SOCIETA' BENEFIT	Revision nr. 7
	Dated 10/11/2022
V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL	Printed on 10/11/2022
	Page n. 7/32
	Replaced revision:6 (Dated: 26/08/2021)

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

CZE	Česká Republika	Nariadení vlády č. 41/2020 Sb. Nariadení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α΄ 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

Dimethyl ether					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
OEL	EU	1920	1000		
Predicted no-effect concentration - PNEC					
Normal value in fresh water				155	µg/l
Normal value in marine water				16	µg/l
Normal value for fresh water sediment				681	µg/kg/d

AMBRO-SOL SRL SOCIETA' BENEFIT						Revision nr. 7		
V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL						Dated 10/11/2022		
						Printed on 10/11/2022		
						Page n. 8/32 Replaced revision:6 (Dated: 26/08/2021)		
Normal value for marine water sediment			69		µg/kg/d			
Normal value of STP microorganisms			160		mg/l			
Normal value for the terrestrial compartment			45		µg/kg/d			
Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers			Effects on workers					
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		NPI				
Inhalation		VND		471 mg/m3		VND		1894 mg/m3
Skin		NPI		NPI		NPI		NPI
Acetone								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	CZE	800	331,2	1500	621			
AGW	DEU	1200	500	2400 (C)	1000 (C)			
MAK	DEU	1200	500	2400	1000			
VLA	ESP	1210	500					
VLEP	FRA	1210	500	2420	1000			
TLV	GRC	1780		3560				
AK	HUN	1210						
VLEP	ITA	1210	500					
VLE	PRT	1210	500					
NDS/NDSch	POL	600		1800				
NPEL	SVK	1210	500					
WEL	GBR	1210	500	3620	1500			
OEL	EU	1210	500					
TLV-ACGIH			250		500			
Predicted no-effect concentration - PNEC								
Normal value in fresh water			10,6		mg/l			
Normal value in marine water			1,06		mg/l			
Normal value for fresh water sediment			30,4		mg/kg			
Normal value for marine water sediment			3,04		mg/kg			
Normal value for water, intermittent release			21		mg/l			
Normal value of STP microorganisms			100		mg/l			
Normal value for the food chain (secondary poisoning)			29,5		mg/kg			
Normal value for the terrestrial compartment			29,5		mg/kg/d			
Normal value for the atmosphere			NPI					
Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers			Effects on workers					
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	62 mg/kg				

Inhalation	VND	200 mg/m3	VND	2,420 mg/m3	VND	1,210 mg/m3
Skin	VND	62 mg/kg			VND	186 mg/kg

N-butyl acetate								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	CZE	950	196,65	1200	248,4			
AGW	DEU	300	62	600 (C)	124 (C)			
VLA	ESP	241	50	724	150			
VLEP	FRA	710	150	940	200			
TLV	GRC	710	150	950	200			
AK	HUN	241		723				
VLEP	ITA	241	50	723	150			
VLE	PRT	241	50	723	150			
NDS/NDSch	POL	240		720				
NPEL	SVK	241	50	723	150			
WEL	GBR	724	150	966	200			
OEL	EU	241	50	723	150			
TLV-ACGIH			50		150			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				180		µg/l		
Normal value in marine water				18		µg/l		
Normal value for fresh water sediment				981		µg/kg/d		
Normal value for marine water sediment				98,1		µg/kg/d		
Normal value of STP microorganisms				35,6		mg/l		
Normal value for the terrestrial compartment				90,3		µg/kg/d		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		2 mg/kg bw/d		2 mg/kg bw/d		2		2
Inhalation	300 mg/m3	300 mg/m3	35,7 mg/m3	12 mg/m3	600 mg/m3	600 mg/m3	300 mg/m3	48 mg/m3
Skin	NPI	6 mg/kg bw/d	NPI	3,4 mg/kg bw/d	NPI	11 mg/kg bw/d	NPI	7 mg/kg bw/d

Xylene (Mixture of isomers)						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200	45,4	400	90,8	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN

AMBRO-SOL SRL SOCIETA' BENEFIT	Revision nr. 7
	Dated 10/11/2022
V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL	Printed on 10/11/2022
	Page n. 11/32
	Replaced revision:6 (Dated: 26/08/2021)

Normal value in fresh water	55,8	mg/l
Normal value in marine water	55,8	mg/l
Normal value for fresh water sediment	284,74	mg/kg/d
Normal value for marine water sediment	284,74	mg/kg/d
Normal value of STP microorganisms	709	mg/l
Normal value for the food chain (secondary poisoning)	1	g/kg
Normal value for the terrestrial compartment	22,5	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral								31 mg/kg bw/d
Inhalation				106 mg/m3				600 mg/m3
Skin				412 mg/kg bw/d				1161 mg/kg bw/d

Hydrocarbons, C9, aromatics								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
OEL	EU	100	19					

Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				11 mg/kg bw/d				
Inhalation				32 mg/m3				150 mg/m3
Skin				11 mg/kg bw/d				25 mg/kg bw/d

2-Butoxyethanol								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	CZE	100	20,4	200	40,8	SKIN		
AGW	DEU	49	10	98 (C)	20 (C)	SKIN		
MAK	DEU	49	10	98	20	SKIN		
VLA	ESP	98	20	245	50	SKIN		
VLEP	FRA	49	10	246	50	SKIN		
TLV	GRC	120	25					
AK	HUN	98		246		SKIN		
VLEP	ITA	98	20	246	50	SKIN		
VLE	PRT	98	20	246	50	SKIN		
NDS/NDSch	POL	98		200		SKIN		
NPEL	SVK	98	20	246	50	SKIN		
WEL	GBR	123	25	246	50	SKIN		
OEL	EU	98	20	246	50	SKIN		

TLV-ACGIH	97	20							
Predicted no-effect concentration - PNEC									
Normal value in fresh water				8,8	mg/l				
Normal value in marine water				880	µg/l				
Normal value for fresh water sediment				34,6	mg/kg/d				
Normal value for water, intermittent release				9,1	mg/l				
Normal value of STP microorganisms				463	mg/l				
Normal value for the food chain (secondary poisoning)				20	mg/kg				
Normal value for the terrestrial compartment				2,33	mg/kg/d				
Health - Derived no-effect level - DNEL / DMEL									
	Effects on consumers					Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Oral		26,7 mg/kg bw/d		6,3 mg/kg bw/d					
Inhalation	147 mg/m3	426 mg/m3	NPI	59 mg/m3	246 mg/m3	1091 mg/m3	NPI	98 mg/m3	
Skin	VND	89 mg/kg bw/d	NPI	75 mg/kg bw/d	VND	89 mg/kg bw/d	NPI	125 mg/kg bw/d	
Solvent naphtha (petroleum), light arom.									
Health - Derived no-effect level - DNEL / DMEL									
	Effects on consumers					Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Inhalation				32 mg/m3					
Skin				11 mg/kg					
2-methoxy-1-methylethyl acetate									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
TLV	CZE	270	49,14	550	100,1	SKIN			
AGW	DEU	270	50	270	50				
MAK	DEU	270	50	270	50				
VLA	ESP	275	50	550	100	SKIN			
VLEP	FRA	275	50	550	100	SKIN			
TLV	GRC	275	50	550	100				
AK	HUN	275		550					
VLEP	ITA	275	50	550	100	SKIN			
VLE	PRT	275	50	550	100	SKIN			
NDS/NDSch	POL	260		520		SKIN			
NPEL	SVK	275	50	550	100	SKIN			
WEL	GBR	274	50	548	100	SKIN			
OEL	EU	275	50	550	100	SKIN			
Predicted no-effect concentration - PNEC									
Normal value in fresh water				635	µg/l				
Normal value in marine water				63,5	µg/l				

Normal value for fresh water sediment	3,29	mg/kg/d
Normal value for marine water sediment	329	µg/kg/d
Normal value of STP microorganisms	100	mg/l
Normal value for the terrestrial compartment	290	µg/kg soil dw

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		36 mg/kg bw/d				
Inhalation	NPI	NPI	33 mg/m3	33 mg/m3	550 mg/m3	NPI	NPI	275 mg/m3
Skin	NPI	NPI	NPI	320 mg/kg bw/d	NPI	NPI	NPI	796 mg/kg bw/d

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	10				
VLEP	FRA	10				
TLV	GRC		10			
NDS/NDSch	POL	10				INHAL
NPEL	SVK	5				
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0,2				RESP

Ethylbenzene						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200	45,4	500	113,5	SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
TLV	GRC	435	100	545	125	
AK	HUN	442		884		SKIN
VLEP	ITA	442	100	884	200	SKIN
VLE	PRT	442	100	884	200	SKIN
NDS/NDSch	POL	200		400		SKIN
NPEL	SVK	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

Predicted no-effect concentration - PNEC
--

AMBRO-SOL SRL SOCIETA' BENEFIT						Revision nr. 7		
V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL						Dated 10/11/2022		
						Printed on 10/11/2022		
						Page n. 14/32 Replaced revision:6 (Dated: 26/08/2021)		
Normal value in fresh water		100		µg/l				
Normal value in marine water		55		µg/l				
Normal value for fresh water sediment		13,7		mg/kg/d				
Normal value for marine water sediment		1,37		mg/kg/d				
Normal value for water, intermittent release		55		µg/l				
Normal value of STP microorganisms		9,6		mg/l				
Normal value for the food chain (secondary poisoning)		20		mg/kg				
Normal value for the terrestrial compartment		2,68		mg/kg/d				
Health - Derived no-effect level - DNEL / DMEL								
		Effects on consumers			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		1,6 mg/kg bw/d				1,6
Inhalation	NPI	VND	NPI	15 mg/m3	293 mg/m3	VND	NPI	77 mg/m3
Skin		NPI		NPI	NPI	NPI	NPI	180 mg/kg bw/d
Isobutyl acetate								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	CZE	950	196,65	1200	248,4			
AGW	DEU	300	62	600 (C)	124 (C)			
VLA	ESP	724	150					
VLEP	FRA	710	150	940	200			
TLV	GRC	950	200	950	200			
AK	HUN	241		723				
VLEP	ITA	241	50	723	150			
VLE	PRT	241	50	723	150			
NDS/NDSch	POL	240		720				
NPEL	SVK	241	50	723	150			
WEL	GBR	724	150	903	187			
OEL	EU	241	50	723	150			
TLV-ACGIH			50		150			
Predicted no-effect concentration - PNEC								
Normal value in fresh water		170		µg/l				
Normal value in marine water		17		µg/l				
Normal value for fresh water sediment		877		µg/kg/d				
Normal value for marine water sediment		87,7		µg/kg/d				
Normal value of STP microorganisms		200		mg/l				
Normal value for the terrestrial compartment		75,5		µg/kg/d				
Health - Derived no-effect level - DNEL / DMEL								
		Effects on consumers			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic

Oral	5 mg/kg bw/d			5 mg/kg bw/d				
Inhalation	300 mg/m3		35,7 mg/m3	35,7 mg/m3	600 mg/m3	600 mg/m3	300 mg/m3	300 mg/m3
Skin	NPI	5 mg/kg bw/d	NPI	5 mg/kg bw/d	NPI	10 mg/kg bw/d	NPI	10 mg/kg bw/d

Cetrimonium chloride								
Predicted no-effect concentration - PNEC								
Normal value in fresh water			680		ng/l			
Normal value in marine water			68		ng/l			
Normal value for fresh water sediment			9,27		mg/kg/d			
Normal value for marine water sediment			927		µg/kg/d			
Normal value of STP microorganisms			400		µg/l			
Normal value for the terrestrial compartment			7		mg/kg/d			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		VND		2,83 mg/kg bw/d				
Inhalation	NPI	NPI	NPI	980 µg/m3	NPI	NPI	NPI	3,32 mg/m3
Skin	VND	VND	VND	2,83 mg/kg bw/d	VND	VND	VND	4,7 mg/kg bw/d

Reaction mass of ethylbenzene and xylene								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				327	µg/l			
Normal value in marine water				327	µg/l			
Normal value for fresh water sediment				12,46	mg/kg/d			
Normal value for marine water sediment				12,46	mg/kg/d			
Normal value for water, intermittent release				327	µg/l			
Normal value of STP microorganisms				6,58	mg/l			
Normal value for the terrestrial compartment				2,31	mg/kg/d			
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				1,6 mg/kg bw/d				
Inhalation				14,8 mg/m3	289 mg/m3			77 mg/m3
Skin				108 mg/kg bw/d				180 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

AMBRO-SOL SRL SOCIETA' BENEFIT

Revision nr. 7

Dated 10/11/2022

Printed on 10/11/2022

Page n. 16/32

Replaced revision:6 (Dated: 26/08/2021)

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	aerosol	
Colour	various	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	flammable gas	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	< 0 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	Reason for missing data: substance/mixture is non-polar/aprotic (eg: an organic solvent mixture)
Kinematic viscosity	Da 12`` a 15`` Coppa Ford	
Solubility	insoluble in water	

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	0,78 kg/l	Temperature: 20 °C
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) :	94,95 %	-	712,00	g/litre
VOC (volatile carbon)	51,50 %	-	401,68	g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

N-butyl acetate

Decomposes on contact with: water.

Ethyl methyl ketone

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

2-Butoxyethanol

Decomposes under the effect of heat.

2-methoxy-1-methylethyl acetate

Stable in normal conditions of use and storage. On contact with: strong oxidising agents.

With the air it may slowly develop peroxides that explode with an increase in temperature.

Isobutyl acetate

Decomposes under the effect of heat. Attacks various types of plastic materials.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

No hazardous reactions are foreseeable in normal conditions of use and storage.

Acetone

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

N-butyl acetate

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

Xylene (Mixture of isomers)

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.

Ethyl methyl ketone

May form peroxides with: air,light,strong oxidising agents.Risk of explosion on contact with: hydrogen peroxide,nitric acid,sulphuric acid.May react dangerously with: oxidising agents,trichloromethane,alkalis.Forms explosive mixtures with: air.

2-Butoxyethanol

May react dangerously with: aluminium,oxidising agents.Forms peroxides with: air.

2-methoxy-1-methylethyl acetate

May react violently with: oxidising substances,strong acids,alkaline metals.

Ethylbenzene

Reacts violently with: strong oxidants.Attacks various types of plastic materials.May form explosive mixtures with: air.

Isobutyl acetate

Risk of explosion on contact with: strong oxidising agents.May react violently with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating.

Acetone

Avoid exposure to: sources of heat,naked flames.

N-butyl acetate

Avoid exposure to: moisture,sources of heat,naked flames.

AMBRO-SOL SRL SOCIETA' BENEFIT	Revision nr. 7
	Dated 10/11/2022
V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL	Printed on 10/11/2022
	Page n. 19/32 Replaced revision:6 (Dated: 26/08/2021)

Ethyl methyl ketone
Avoid exposure to: sources of heat.
2-Butoxyethanol
Avoid exposure to: sources of heat,naked flames.
Isobutyl acetate
Avoid exposure to: sources of heat,naked flames.
10.5. Incompatible materials
Strong reducing or oxidising agents, strong acids or alkalis, hot material.
Acetone
Incompatible with: acids,oxidising substances.
N-butyl acetate
Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.
Ethyl methyl ketone
Incompatible with: strong oxidants,inorganic acids,ammonia,copper,chloroform.
2-Butoxyethanol
Keep away from: strong oxidants.
2-methoxy-1-methylethyl acetate
Incompatible with: oxidising substances,strong acids,alkaline metals.
Isobutyl acetate
Incompatible with: strong oxidants,nitrates,strong acids,strong bases.
10.6. Hazardous decomposition products
Acetone
May develop: ketenes,irritant substances.
2-Butoxyethanol
May develop: hydrogen.
Ethylbenzene
May develop: methane,styrene,hydrogen,ethane.

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL****SECTION 11. Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information

2-methoxy-1-methylethyl acetate

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

N-butyl acetate

WORKERS: inhalation; contact with the skin.

Xylene (Mixture of isomers)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

2-methoxy-1-methylethyl acetate

WORKERS: inhalation; contact with the skin.

Ethylbenzene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

N-butyl acetate

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Xylene (Mixture of isomers)

Toxic action on the central nervous system (encephalopathies); irritant action on the skin, conjunctiva, cornea and respiratory system.

2-methoxy-1-methylethyl acetate

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

Ethylbenzene

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispeš). Is irritating for skin, conjunctiva and respiratory tract.

Interactive effects

N-butyl acetate

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

Xylene (Mixture of isomers)

Alcohol intake interferes with the metabolism of the substance, inhibiting it. Consumption of ethanol (0.8 g / kg) before a 4-hour exposure to xylenes vapors (145 and 280 ppm) causes a 50% decrease in the excretion of metilippuric acid, while the blood concentration of xylenes rises about 1.5-2 times. At the same time, there is an increase in the secondary side effects of ethanol. The metabolism of xylenes is enhanced by phenobarbital and 3-methyl-colanthrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with glycine, which results in a decrease in urinary excretion of metilippuric acid. Other industrial products can interfere with the metabolism of xylenes.

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

Dimethyl ether

LC50 (Inhalation mists/powders):	164000 ppm rat
----------------------------------	----------------

Acetone

LD50 (Dermal):	7426 mg/kg bw guinea pig
LD50 (Oral):	5800 mg/kg bw
LC50 (Inhalation vapours):	> 20 mg/l/4h air

N-butyl acetate

LD50 (Dermal):	> 5000 mg/kg rabbit
LD50 (Oral):	> 10000 mg/kg Rat
LC50 (Inhalation vapours):	0,74 mg/l/4h Rat

Xylene (Mixture of isomers)

LD50 (Dermal):	> 1700 mg/kg rabbit
LD50 (Oral):	> 3000 mg/kg rat
LC50 (Inhalation vapours):	5000 ppm/4h rat
STA (Inhalation mists/powders):	1,5 mg/l

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

(figure used for calculation of the acute toxicity estimate of the mixture)

Ethyl methyl ketone

LD50 (Dermal): 10 ml/kg rabbit
LD50 (Oral): > 2000 mg/kg rat

Hydrocarbons, C9, aromatics

LD50 (Dermal): > 3000 mg/kg bw rabbit
LD50 (Oral): > 4 ml/kg bw rat

2-Butoxyethanol

LD50 (Oral): 1200 mg/kg Guinea pig
LC50 (Inhalation vapours): 3 mg/l/4h Rat
STA (Inhalation mists/powders): 0,501 mg/l
(figure used for calculation of the acute toxicity estimate of the mixture)

Solvent naphtha (petroleum), light arom.

LD50 (Dermal): > 2000 mg/kg bw rabbit
LD50 (Oral): > 2000 mg/kg bw rat

2-methoxy-1-methylethyl acetate

LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): > 5000 mg/kg Rat
LC50 (Inhalation vapours): 1805,05 ppm LC0 (4 h) rat

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

LD50 (Oral): > 10000 mg/kg Rat

Ethylbenzene

LD50 (Dermal): 15354 mg/kg Rabbit
LD50 (Oral): 3500 mg/kg Rat
LC50 (Inhalation vapours): 17,2 mg/l/4h Rat
STA (Inhalation mists/powders): 1,5 mg/l
(figure used for calculation of the acute toxicity estimate of the mixture)

Isobutyl acetate

LD50 (Dermal): 17400 mg/kg bw rabbit
LD50 (Oral): 13413 mg/kg bw rat
LC50 (Inhalation vapours): 30 mg/l/6h rat

SKIN CORROSION / IRRITATION

Causes skin irritation

AMBRO-SOL SRL SOCIETA' BENEFIT

Revision nr. 7

Dated 10/11/2022

Printed on 10/11/2022

Page n. 23/32

Replaced revision:6 (Dated: 26/08/2021)

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Xylene (Mixture of isomers)

Classified in group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).

The US Environmental Protection Agency (EPA) claims that "the data were found to be inadequate for an assessment of carcinogenic potential."

Titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$]

The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1% or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

Ethylbenzene

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).

Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Dimethyl ether

LC50 - for Fish	> 4000 mg/l/96h <i>Poecilia reticulata</i>
EC50 - for Crustacea	> 4000 mg/l/48h <i>Daphnia magna</i>
Chronic NOEC for Fish	4,1 g/l 4 days
Chronic NOEC for Crustacea	4,4 g/l 48 h

2-methoxy-1-methylethyl acetate

LC50 - for Fish	> 100 mg/l/96h
EC50 - for Crustacea	> 100 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h
Chronic NOEC for Fish	> 10 mg/l 14 days
Chronic NOEC for Crustacea	100 mg/l
Chronic NOEC for Algae / Aquatic Plants	1 g/l 4 days

Ethylbenzene

LC50 - for Fish	4,65 mg/l/96h
EC50 - for Crustacea	2,1 mg/l/48h
EC50 - for Algae / Aquatic Plants	5,15 mg/l/72h
Chronic NOEC for Fish	3,3 mg/l 4 days
Chronic NOEC for Crustacea	960 µg/l 7 days
Chronic NOEC for Algae / Aquatic Plants	3,95 mg/l 4 days

2-Butoxyethanol

LC50 - for Fish	1,474 g/l
EC50 - for Crustacea	1,55 g/l

AMBRO-SOL SRL SOCIETA' BENEFIT

Revision nr. 7

Dated 10/11/2022

Printed on 10/11/2022

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

Page n. 25/32

Replaced revision:6 (Dated: 26/08/2021)

EC50 - for Algae / Aquatic Plants	911 mg/l/72h
EC10 for Crustacea	134 mg/l 21 days
Chronic NOEC for Fish	100 mg/l 21 days
Chronic NOEC for Crustacea	100 mg/l 21 days
Chronic NOEC for Algae / Aquatic Plants	88 mg/l 72 h

Acetone

LC50 - for Fish	6,83 g/l
EC50 - for Crustacea	8,8 g/l/48h
Chronic NOEC for Crustacea	1,659 g/l 28 days

Ethyl methyl ketone

LC50 - for Fish	2,9 g/l/96h
EC50 - for Crustacea	308 mg/l/48h
EC50 - for Algae / Aquatic Plants	1,97 g/l/72h
Chronic NOEC for Crustacea	68 mg/l 48 h

N-butyl acetate

LC50 - for Fish	18 mg/l/96h
EC50 - for Crustacea	32 mg/l/48h
EC50 - for Algae / Aquatic Plants	246 mg/l/72h
Chronic NOEC for Crustacea	23,2 mg/l 21 days
Chronic NOEC for Algae / Aquatic Plants	105 mg/l 72 h

Isobutyl acetate

LC50 - for Fish	16,6 mg/l/96h
EC50 - for Crustacea	24,6 mg/l/48h
EC50 - for Algae / Aquatic Plants	321,5 mg/l/72h
Chronic NOEC for Crustacea	23,2 mg/l 21 days
Chronic NOEC for Algae / Aquatic Plants	1505 mg/l 72 h

Hydrocarbons, C9, aromatics

EC50 - for Algae / Aquatic Plants	> 290 µg/l/72h
Chronic NOEC for Algae / Aquatic Plants	70 µg/l 72 h

12.2. Persistence and degradability**2-methoxy-1-methylethyl acetate**

Easily biodegradable. It is rapidly oxidized into the air by photochemical reaction.

Dimethyl ether

NOT rapidly degradable

Under test conditions no biodegradation observed (100%)

Xylene (Mixture of isomers)

Solubility in water 100 - 1000 mg/l

Rapidly degradable

Titanium dioxide; [in powder form containing

AMBRO-SOL SRL SOCIETA' BENEFIT		Revision nr. 7
V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL		Dated 10/11/2022
		Printed on 10/11/2022
		Page n. 26/32
		Replaced revision:6 (Dated: 26/08/2021)
1 % or more of particles with aerodynamic diameter ≤ 10 µm]		
Solubility in water	< 0,001 mg/l	
Degradability: information not available		
2-methoxy-1-methylethyl acetate		
Solubility in water	> 10000 mg/l	
Rapidly degradable		
Ethylbenzene		
Solubility in water	1000 - 10000 mg/l	
Rapidly degradable		
2-Butoxyethanol		
Solubility in water	1000 - 10000 mg/l	
Rapidly degradable		
Acetone		
Rapidly degradable		
Ethyl methyl ketone		
Solubility in water	> 10000 mg/l	
Rapidly degradable		
N-butyl acetate		
Solubility in water	5,3 g/l	
Rapidly degradable		
Isobutyl acetate		
Solubility in water	1000 - 10000 mg/l	
Rapidly degradable		
Solvent naphtha (petroleum), light arom.		
Degradability: information not available		
Hydrocarbons, C9, aromatics		
Rapidly degradable		
12.3. Bioaccumulative potential		
Xylene (Mixture of isomers)		
Partition coefficient: n-octanol/water	3,12	
BCF	25,9	
2-methoxy-1-methylethyl acetate		
Partition coefficient: n-octanol/water	1,2	
Ethylbenzene		
Partition coefficient: n-octanol/water	3,6	
2-Butoxyethanol		
Partition coefficient: n-octanol/water	0,81	
Acetone		
Partition coefficient: n-octanol/water	-0,23	
BCF	3	

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

Ethyl methyl ketone

Partition coefficient: n-octanol/water 0,3

N-butyl acetate

Partition coefficient: n-octanol/water 2,3

BCF 15,3

Isobutyl acetate

Partition coefficient: n-octanol/water 2,3

BCF 15,3

12.4. Mobility in soil

Xylene (Mixture of isomers)

Partition coefficient: soil/water 2,73

N-butyl acetate

Partition coefficient: soil/water < 3

Solvent naphtha (petroleum), light arom.

Partition coefficient: soil/water 1,78

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Dimethyl ether

Given the high rate of disappearance of the solution, the product is unlikely to constitute a significant hazard to aquatic life. Destructive effect on ozone: 0. Global warming potential (GWP): 1.

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

Product residues are to be considered special hazardous waste.
Empty cans, even if completely emptied, must not be dispersed in the environment.
The aerosol container overheated to a temperature above 50 ° C may burst even if it contains a small residue of gas.
Disposal must take place in an authorized place and in compliance with the laws in force.
The transport of waste may be subject to ADR.
European waste catalog code (contaminated containers):
Aerosol as domestic waste is excluded from the application of the aforementioned rule.
The exhausted aerosol for professional / industrial use can be classified:
15.01.11 *: metallic packaging containing dangerous solid porous matrices, including empty pressure containers.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1
IMDG: Class: 2 Label: 2.1
IATA: Class: 2 Label: 2.1

**14.4. Packing group**

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: --
Special provision: -

Limited
Quantities: 1
L

Tunnel
restriction
code: (D)

AMBRO-SOL SRL SOCIETA' BENEFIT		Revision nr. 7
V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL		Dated 10/11/2022
		Printed on 10/11/2022
		Page n. 29/32 Replaced revision:6 (Dated: 26/08/2021)

IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 40

Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**
Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Special finishes.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Press. Gas	Pressurised gas
Carc. 2	Carcinogenicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H351	Suspected of causing cancer.
H331	Toxic if inhaled.

<p align="center">AMBRO-SOL SRL SOCIETA' BENEFIT</p>	<p>Revision nr. 7 Dated 10/11/2022</p>
<p align="center">V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml AMBRO-SOL</p>	<p>Printed on 10/11/2022 Page n. 31/32 Replaced revision:6 (Dated: 26/08/2021)</p>

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH212	Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament

**V400/CAR - FINISHES BODYWORK AGRICULTURE LINE 400 ml
AMBRO-SOL**

9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 11 / 12 / 15 / 16.