



DECLARATION OF PERFORMANCE
No. B2003G/2018

Unique identification code of the product-type:

1200 Gauge PE film Damp proof membrane Type A

Intended use/es:

Flexible sheets for waterproofing. Plastic and rubber damp proof sheets including plastic and rubber tanking basement sheet.
Damp proof sheet.

System/s of AVCP:

system 3 and system 4 for reaction to fire

Harmonised standard:

EN 13967:2012 Flexible sheets for waterproofing – Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheet – Definitions and characteristics.

Notified body/ies:

Polish Research and Certification Center S.A., ul. Wejhera 18a, 80-346 Gdańsk; nr 1434

Declared performance/s:

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
Reaction to the fire	class F	EN 13967:2012
Water tightness	Pass at 2 kPa	
Water vapour transmission (μ)	185 000 +/- 30%	
Resistance to impact	NPD	
Joint strength along/across	≥ 135 / ≥ 140	
Tensile strenght: Tensile force: along/across Elongation: along/across	≥ 100 N/50mm / ≥ 80 N/50mm $\geq 350\%$ / $\geq 350\%$	
Tear strenght: along/across	≥ 60 N / ≥ 60 N	
Resistance: - against ageing - to alkali	Pass at 2 kPa Pass at 2 kPa	
Dengerous substances	NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.