

WD-40 SPECIALIST[®] SILICONE

DATA
SHEET



PRODUCT OVERVIEW

WD-40[®] Specialist[®] Silicone Lubricant is a non-staining, hard working formula which provides excellent lubrication, won't attract dirt, and protects against moisture. It stops parts from sticking and can be used on high pressure equipment. This product can be used on **metal, plastic, wood and rubber**.



NARROW SPRAY



WIDE SPRAY

FEATURES & BENEFITS

- Dual action Smart Straw[®] applicator for wide area and precision spray applications
- Excellent lubrication on plastics, rubber, wood and metal
- Formulated for improved high pressure performance
- Waterproofs and protects against moisture
- Prevents rust and corrosion
- Eliminates sticking and binding
- Non-staining
- Temperature range: -35°C to +200°C

RECOMMENDED FOR:

Belts, Bearings, Linkages, Doors & Hinges, Tools, Guide Rails, Valves and Locks & Hoists.

DIRECTIONS FOR USE

Shake can well. Apply by spraying directly on surface to be lubricated and protected.

TECHNICAL DATA

| | |
|------------------|---------------------------------|
| Appearance | Clear yellow liquid |
| SG | 0.79 - 0.80 |
| Discharge Rate | 0.7 - 1.2 g/s |
| Solubility | Not miscible with water |
| NSF Category | H2 |
| Flammability | Classed as extremely flammable |
| Lubrication | Scar depth 0.68mm (ASTM D-4172) |
| Extreme Pressure | 816lb (ASTM 3233) |

