

STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

Issue date: 17.07.2023 Version: 0.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

1.2. Relevant identified uses of the substance or mixture and uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

NUCLEUS INCORPORATED
13901 WILLARD RD, CHANTILLY, VA 20151
+1 703 988 7773

1.4. Emergency telephone number

For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

| | |
|---|------|
| Flammable aerosol Category 1 | H222 |
| Acute toxicity (inhalation:gas) Category 4 | H332 |
| Skin corrosion/irritation Category 2 | H315 |
| Serious eye damage/eye irritation Category 2A | H319 |
| Respiratory sensitisation Category 1 | H334 |
| Skin sensitization Category 1 | H317 |
| Carcinogenicity Category 2 | H351 |
| Specific target organ toxicity (single exposure) Category 3 | H335 |
| Specific target organ toxicity (repeated exposure) Category 2 | H373 |

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H222 - Extremely flammable aerosol
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames. - No smoking
P211 - Do not spray on an open flame or other ignition source

STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

Issue date: 17.07.2023 Version: 0.0

P251 - Pressurized container: Do not pierce or burn, even after use
 P261 - Avoid breathing gas, spray, vapors
 P280 - Wear eye protection, face protection, protective clothing, protective gloves
 P284 - [In case of inadequate ventilation] wear respiratory protection
 P302+P352 - If on skin: Wash with plenty of water
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | GHS-US classification |
|--|--------------------|----------|---|
| Isocyanic acid, polymethylenepolyphenylene ester | (CAS No) 9016-87-9 | 20 - 35 | Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 |
| isobutane | (CAS No) 75-28-5 | 2.5 - 10 | Flam. Gas 1, H220 |
| propane | (CAS No) 74-98-6 | 2.5 - 10 | Flam. Gas 1, H220 |
| dimethyl ether | (CAS No) 115-10-6 | 2.5 - 10 | Flam. Gas 1, H220 |

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

Issue date: 17.07.2023 Version: 0.0

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurized container: may burst if heated.
Reactivity : Extremely flammable aerosol. Pressurized container: may burst if heated.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| USA - ACGIH - Occupational Exposure Limits | |
|--|----------------------------------|
| Local name | Propane |
| ACGIH STEL (ppm) | 1000 ppm (EX - Explosion hazard) |
| Remark (ACGIH) | TLV® Basis: Simple Asphyxiant |

STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

Issue date: 17.07.2023 Version: 0.0

| | |
|---|----------------------------------|
| Regulatory reference | ACGIH 2020 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Propane |
| OSHA PEL (TWA) (mg/m ³) | 1800 mg/m ³ |
| OSHA PEL (TWA) (ppm) | 1000 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) | |
| No additional information available | |
| isobutane (75-28-5) | |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Isobutane |
| ACGIH STEL (ppm) | 1000 ppm (EX - Explosion hazard) |
| Remark (ACGIH) | TLV® Basis: CNS impair |
| Regulatory reference | ACGIH 2020 |
| propane (74-98-6) | |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Propane |
| Remark (ACGIH) | TLV® Basis: Simple Asphyxiant |
| Regulatory reference | ACGIH 2020 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Propane |
| OSHA PEL (TWA) (mg/m ³) | 1800 mg/m ³ |
| OSHA PEL (TWA) (ppm) | 1000 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
 Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves. EN 374. Nitrile rubber gloves

Eye protection:

Chemical goggles or safety glasses. EN 166.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. EN 14387

Personal protective equipment symbol(s):



STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

Issue date: 17.07.2023 | Version: 0.0

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Gas |
| Appearance | : Liquid under pressure. |
| Color | : Dark Grey |
| Odor | : Characteristic |
| Odor threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : Pressurized container: may burst if heated. |
| Oxidizing properties | : No data available |
| Vapor pressure | : 5 bar |
| Relative density | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Specific gravity / density | : 16 - 25 kg/m ³ |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |

9.2. Other information

VOC content : < 2 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: may burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

Issue date: 17.07.2023 Version: 0.0

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:gas: Harmful if inhaled.

| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) | |
|--|--------------|
| ATE US (gases) | 4500 ppmv/4h |
| ATE US (vapours) | 11 mg/l/4h |
| ATE US (dust,mist) | 1.5 mg/l/4h |

Skin corrosion/irritation : Causes skin irritation.
 Serious eye damage/irritation : Causes serious eye irritation.
 Respiratory or skin sensitization : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
 Germ cell mutagenicity : Not classified
 Carcinogenicity : Suspected of causing cancer.

| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) | |
|--|----------------------|
| IARC group | 3 - Not classifiable |

Reproductive toxicity : Not classified
 Specific target organ toxicity (single exposure) : May cause respiratory irritation.

| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) | |
|--|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) | |
|--|--|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |

Aspiration hazard : Not classified
 Symptoms/injuries after inhalation : May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.
 Symptoms/injuries after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

Issue date: 17.07.2023 Version: 0.0

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Emergency Response Guide (ERG) Number : 126

Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : 1950

Proper Shipping Name (IMDG) : AEROSOLS

Class (IMDG) : 2 - Gases

MFAG-No : 126

Air transport

UN-No. (IATA) : 1950

Proper Shipping Name (IATA) : Aerosols, flammable

Class (IATA) : 2

STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

Issue date: 17.07.2023 Version: 0.0

SECTION 15: Regulatory information

15.1. US Federal regulations

| | |
|--|---|
| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711). |
| isobutane (75-28-5) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313 | |
| propane (74-98-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313 | |

15.2. International regulations

CANADA

| | |
|---|--|
| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| isobutane (75-28-5) | |
| Listed on the Canadian DSL (Domestic Substances List) | |
| propane (74-98-6) | |
| Listed on the Canadian DSL (Domestic Substances List) | |

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

| Component | State or local regulations |
|--|---|
| Isocyanic acid, polymethylenepolyphenylene ester (9016-87-9) | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List |
| isobutane(75-28-5) | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |
| propane(74-98-6) | U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |

SECTION 16: Other information

STANLEY QUICK BOND ADHESIVE PROFESSIONAL FOAM

Issue date: 17.07.2023 Version: 0.0

Full text of H-statements:

| | |
|------|--|
| H220 | Extremely flammable gas. |
| H280 | Contains gas under pressure; may explode if heated. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

SDS US STANLEY

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable